

FRONT

EarthWorks™

Growth products for professional turf management
6-0-0

Cal-Vantage

6-0-0 Liquid Fertilizer
with 8% Calcium & 2% Sulfur

Multiple forms of Calcium
Essential plant nutrients
Improves plant vigor

28 Lbs (12.7Kg - 11.2 lbs./gal.)
(2.5 gallons / 9.5 liters)

BACK

Cal-Vantage

6-0-0 Liquid Fertilizer

with 8% Calcium & 2% Sulfur

Use Instructions

Turf Maintenance

Apply 2 to 8 oz per 1000 sq ft weekly in 2 to 3 gallons of water. Bi-monthly applications can be made at the higher rate on heavier soils. On low CEC soils, a weekly program at the lower rate is suggested. For calcium deficient soils apply up to 8 oz per 1000 sq ft in 3 to 5 gallons of water at weekly intervals during the growing season.

Landscape uses

Apply 4 to 6 oz in 2 gallons of water and drench around the base of trees, shrubs and flower beds every 4 to 8 weeks.

Sodium Removal:

Drench the soil with a solution of 8 to 16 oz per 1000 sq ft in a minimum of 5 gallons of water. Repeat these applications every 2 to 4 weeks until the problem subsides, then revert back to maintenance calcium rates.

Avoid Mixing with excessive phosphorus or sulfur containing materials. Always perform a bench test for compatibility.

Guaranteed Analysis

Total Nitrogen (N)	6.00%
0.90% Ammoniacal Nitrogen	
5.10% Nitrate Nitrogen	
Calcium (Ca)	8.00%
Sulfur (S)	2.00%
2.00% Combined Sulfur (S)	
Boron (B)	0.02%

Derived from: Calcium Nitrate, Ammonium Thiosulfate, Calcium Sulfate, Hydrated Lime, and Sodium Borate.

Information regarding the contents and levels of metals in this product is available on the Internet at <http://www.aapfco.org/metals.htm>

Condition of Sale

1. Seller warrants that this product consists of the ingredients specified and is reasonably fit for the purpose stated on the label when used in accordance with directions under normal conditions of use. No one, other than an officer of Seller, is authorized to make warranty, guarantee or direction concerning this product.
2. Because the time, place, rate of application and other conditions of use are beyond Seller's control, Seller's liability from handling, storage and use of this product is limited to replacement of product or refund of purchase price.

Storage Precautions

Store in manufacturer's containers when possible. If not, store in polyolefin or polyethylene storage tanks. Do not store for extended periods in mild steel and only in approved fiberglass. Although stainless steel tanks are less prone to corrosion than mild steel, they are not recommended for extended storage. Do not use nylon fittings and valves. PVC or polypropylene valves and fittings are recommended.

CAUTION: KEEP OUT OF REACH OF CHILDREN WARNING

Harmful if swallowed. Avoid breathing spray mist. May cause irritation of nose, throat, and/or skin. Avoid contact with the eyes, skin and clothing. If swallowed: induce vomiting by sticking finger down throat. Never give anything by mouth to unconscious person. Get medical attention immediately. If in eyes, wash eyes with plenty of clear water for at least 15 minutes. Get medical attention immediately.

Keep stored above 32°F or 0°C
DO NOT ALLOW TO FREEZE

Guaranteed by:

EarthWorks
1500 Uhler Road
Easton, PA 18040
800 732-TURF
www.earthworksfirst.com

F1399