

Directions for use

Turf (all grasses)

Apply 3-7 pounds of 10-2-5 per 1000 square feet of turf area (.3 to .7 pounds of nitrogen per 1000 sq ft), as needed. This product will not burn when used as directed. For best results, adequate irrigation should be practiced after application and throughout the growing season.

Shrubs (1 to 4 feet of canopy)

Apply 1 pound of 10-2-5 around the base of the plant and lightly work into the soil, being careful not to disturb surface roots. Larger shrubs or stressed plants will benefit from larger feedings.

Trees

For young or small trees (1 to 3 inch diameter) apply 2 to 3 pounds of 10-2-5 per inch of trunk diameter evenly under the canopy drip line. Increase the application rate to 3 to 4 pounds for larger trees. Apply in Spring and Fall, thoroughly watering after each application.

Manufactured for:

EarthWorks
1500 Uhler Road
Easton, PA 18040
www.earthworksfirst.com

Net Weight:

50 pounds
22.68 kilograms

EarthWorks®
10-2-5
Replenish

Standard Grade

Guaranteed Analysis

Total Nitrogen (N) 10.00%
4.20% Ammoniacal Nitrogen
4.55% Water Insoluble Nitrogen*
1.25% Other Water Soluble Nitrogen**

Available Phosphate (P₂O₅) . 2.00%
Soluble Potash (K₂O) 5.00%
Calcium (Ca) 5.75%
Sulfur (S) 6.00%
6.00% Combined Sulfur (S)

Derived from: Composted poultry manure, ammonium sulfate, methylene urea and sulfate of potash.

* 3.40% water insoluble nitrogen from methylene urea.
1.15% water insoluble nitrogen from composted poultry manure

** .80% water soluble nitrogen from methylene urea.
.45% water soluble nitrogen from composted poultry manure

Suggested Spreader Settings
10-2-5 Standard Grade

Spreader	Spread Width	Nitrogen in lb/1000 sq ft	
		0.5	1.0
Spyker	12'	7	8.5
Scott's R8-A (cone 8)	11'	N ½	S ½
AccuPro 2000 (cone 8)	11'	O ½	U
Vicon	28'	37	53
Lely	25'	6.25	8.25

These settings were calibrated and field tested. Age, condition of spreader, speed of operator and evenness of terrain may require adjustment of setting for desired coverage.

Vicon spreader settings are based on 540 rpm and a ground speed of 4.7 mph.

Lely spreader settings are based on 425 rpm and a ground speed of 4.7 mph.

EarthWorks®
 Replenish
10-2-5
 Standard Grade

Pull narrow tape to open →

EarthWorks®
10-2-5
Replenish



Standard Grade
Covers 5,000 square feet
at 1 lb Nitrogen per 1000 sq ft
Prilled

Net Weight:
50 pounds
22.68 kilograms

Standard Grade
EarthWorks®
 Replenish
10-2-5