

Directions for use

Turf (all grasses)

Apply 10-25 pounds of 3-4-3 per 1000 square feet of turf area (.3 to .75 pounds of nitrogen per 1000 sq ft) as needed. This product will not burn when used as directed. For best results, adequate irrigation should be practiced after application and throughout the growing season.

Shrubs (1 to 4 feet of canopy)

Apply 2 pounds of 3-4-3 around the base of the plant and lightly work into the soil, being careful not to disturb surface roots. Larger shrubs or stressed plants will benefit from larger feedings.

Trees

For young or small trees (1 to 3 inch diameter) apply 5 to 10 pounds of 3-4-3 per inch of trunk diameter evenly under the canopy drip line. Increase the application rate to 10 to 15 pounds for larger trees. Apply in Spring and Fall, thoroughly watering after each application.

Manufactured for:

EarthWorks
1500 Uhler Road
Easton, PA 18040

www.earthworksfirst.com

Net Weight:

50 pounds

22.68 kilograms

EarthWorks®

3-4-3

Replenish

Standard Grade

Bedding Plants

Annuals, perennials and bulbs require nutrients at different rates which makes a specific recommendation difficult. Apply 3-4-3 not less than 10 pounds per 100 square feet of flower bed. Broadcast beds prior to planting and work product into the top 3 inches of the soil. To help maintain peak appearance of the plants, side dress 3-4-3 during the growing season at 5 pounds

Guaranteed Analysis

Total Nitrogen (N) 3.00%
2.30% Water Insoluble Nitrogen
.70% Water Soluble Nitrogen
Available Phosphate (P₂O₅) . 4.00%
Soluble Potash (K₂O) 3.00%
Derived from: Composted poultry manure.

**Suggested Spreader Settings
3-4-3 Standard Grade**

Spreader	Spread Width	Nitrogen in lb/1000 sq ft	
		0.25	0.50
Spyker	11'	7.2	9.3
Scott's R8-A (cone 8)	10'	O 1/2	Q
AccuPro 2000 (cone 8)	10'	P	V 1/2
Vicon	28'	43	65
Lely	25'	7	9.5

These settings were calibrated and field tested. Age, condition of spreader, speed of operator and evenness of terrain may require adjustment of setting for desired coverage.

Vicon spreader settings are based on 540 rpm and a ground speed of 4.7 mph.

Lely spreader settings are based on 425 rpm and a ground speed of 4.7 mph.

EarthWorks®
 Replenish
3-4-3
 Standard Grade

Pull narrow tape to open →

EarthWorks®

3-4-3

Replenish



Standard Grade

Covers 5,000 square feet
at .3 lb Nitrogen per 1000 sq ft

Prilled

Net Weight:

50 pounds

22.68 kilograms

Standard Grade
EarthWorks®
 Replenish
3-4-3